# Material Safety Data Sheet

### Nitrogen

## Section 1. Chemical product and company identification

Product name : Nitrogen

Supplier : Chemtron Science Laboratories Pvt. Ltd.

EL-47 Electronics Zone

Mahape MIDC Navi Mumbai India.400710

Product use : Synthetic/Analytical chemistry. Liquid - cryogenic coolant.

Synonym : nitrogen (dot); nitrogen gas; Nitrogen NF, LIN, Cryogenic Liquid Nitrogen, Liquid

Nitrogen

MSDS # : CSL-1040

Date of Preparation/ : 11/22/2013.

Revision

In case of emergency

: +9122-67847300

# Section 2. Hazards identification

Physical state : Gas. [NORMALLY A COLORLESS GAS: MAY BE A CLEAR COLORLESS LIQUID AT

LOW TEMPERATURES. SOLD AS A COMPRESSED GAS OR LIQUID IN STEEL

CYLINDERS.1

**Emergency overview** : WARNING!

GAS:

CONTENTS UNDER PRESURE.

Do not puncture or incinerate container.

Can cause rapid suffocation. May cause severe frostbite.

LIQUID:

Extremely cold liquid and gas under pressure.

Can cause rapid suffocation. May cause severe frostbite.

Do not puncture or incinerate container. May cause target organ damage, based on

animal data.

Contact with rapidly expanding gases or liquids can cause frostbite.

**Target organs**: May cause damage to the following organs: lungs.

Routes of entry : Inhalation

Potential acute health effects

Eyes : Contact with rapidly expanding gas may cause burns or frostbite. Contact with cryogenic

liquid can cause frostbite and cryogenic burns.

**Skin** : Contact with rapidly expanding gas may cause burns or frostbite. Contact with cryogenic

liquid can cause frostbite and cryogenic burns.

**Inhalation** : Acts as a simple asphyxiant.

Ingestion : Ingestion is not a normal route of exposure for gases. Contact with cryogenic liquid can

cause frostbite and cryogenic burns.

Potential chronic health effects

**Chronic effects**: May cause target organ damage, based on animal data.

Target organs: May cause damage to the following organs: lungs.

Medical conditions aggravated by overexposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

Build 1.1 Page: 1/6

Nitrogen

**Eye contact** 

See toxicological information (Section 11)

# Section 3. Composition, Information on Ingredients

Name CAS number % Volume Exposure limits

Nitrogen 7727-37-9 99+ Oxygen Depletion [Asphyxiant]

### Section 4. First aid measures

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact : None expected.

Frostbite : Try to warm up the frozen tissues and seek medical attention.

Inhalation : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention

immediately.

**Ingestion**: As this product is a gas, refer to the inhalation section.

### Section 5. Fire-fighting measures

Flammability of the product : Non-flammable.

**Products of combustion**: Decomposition products may include the following materials:

nitrogen oxides

**Fire-fighting media and** : Use an extinguishing agent suitable for the surrounding fire. **instructions** 

Apply water from a safe distance to cool container and protect surrounding area. If involved in fire, shut off flow immediately if it can be done without risk.

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water

Contains gas under pressure. In a fire or if heated, a pressure increase will occur and

the container may burst or explode.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (section 8). Shut off gas supply if this can be done safely.

Isolate area until gas has dispersed.

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains

and sewers.

**Methods for cleaning up** : Immediately contact emergency personnel. Stop leak if without risk. Note: see Section

1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Handling

: High pressure gas. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

Never allow any unprotected part of the body to touch uninsulated pipes or vessels that contain cryogenic liquids. Prevent entrapment of liquid in closed systems or piping without pressure relief devices. Some materials may become brittle at low temperatures and will easily fracture.

Build 1.1 Page: 2/6

### Nitrogen

#### Storage

Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

For additional information concerning storage and handling refer to Compressed Gas Association pamphlets P-1 Safe Handling of Compressed Gases in Containers and P-12 Safe Handling of Cryogenic Liquids available from the Compressed Gas Association,

# Section 8. Exposure controls/personal protection

### **Engineering controls**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### Personal protection

**Eyes** 

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

When working with cryogenic liquids, wear a full face shield.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

The applicable standards are (US) 29 CFR 1910.134 and (Canada) Z94.4-93

**Hands** 

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Insulated gloves suitable for low temperatures

Personal protection in case

of a large spill

Self-contained breathing apparatus (SCBA) should be used to avoid inhalation of the

product.

**Product name** 

Nitrogen

Oxygen Depletion [Asphyxiant]

Consult local authorities for acceptable exposure limits.

### Section 9. Physical and chemical properties

**Molecular weight** : 28.02 g/mole

**Molecular formula** N2

**Boiling/condensation point** : -195.79°C (-320.4°F) **Melting/freezing point** : -210.01°C (-346°F) -146.9°C (-232.4°F) Critical temperature

0.967 (Air = 1) Liquid Density@BP: 50.46 lb/ft3 (808.3 kg/m3) Vapor density

Specific Volume (ft 3/lb) 13.8889 Gas Density (lb/ft 3) 0.072

# Section 10. Stability and reactivity

Stability and reactivity

: The product is stable.

**Hazardous decomposition** products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Hazardous polymerization** 

: Under normal conditions of storage and use, hazardous polymerization will not occur.

Build 1.1 Page: 3/6

# Section 11. Toxicological information

**Toxicity data** 

**Chronic effects on humans**: May cause damage to the following organs: lungs.

Other toxic effects on humans

: No specific information is available in our database regarding the other toxic effects of this material to humans.

Specific effects

Carcinogenic effects : No known significant effects or critical hazards.

Mutagenic effects : No known significant effects or critical hazards.

Reproduction toxicity : No known significant effects or critical hazards.

# Section 12. Ecological information

### **Aquatic ecotoxicity**

Not available.

**Environmental fate** : Not available.

**Environmental hazards** : No known significant effects or critical hazards.

Toxicity to the environment : Not available.

### Section 13. Disposal considerations

Product removed from the cylinder must be disposed of in accordance with appropriate Federal, State, local regulation.Return cylinders with residual product to ChemtronDo not dispose of locally.

# Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	UN1066	NITROGEN, COMPRESSED	2.2	Not applicable (gas).		Limited quantity Yes.
	UN1977	Nitrogen, refrigerated liquid				Packaging instruction Passenger aircraft Quantity limitation: 75 kg  Cargo aircraft Quantity limitation: 150 kg
TDG Classification	UN1066 UN1977	NITROGEN, COMPRESSED Nitrogen, refrigerated liquid	2.2	Not applicable (gas).		Explosive Limit and Limited Quantity Index 0.125  Passenger Carrying Road or Rail Index 75

Build 1.1 Page: 4/6

Nitrogen										
Mexico Classification	UN1066	NITROGEN, COMPRESSED	2.2	Not applicable (gas).		-				
	UN1977	Nitrogen, refrigerated liquid			65.					

<sup>&</sup>quot;Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

# Section 15. Regulatory information

### **United States**

U.S. Federal regulations

: TSCA 8(a) CDR Exempt/Partial exemption: This material is listed or exempted.

United States inventory (TSCA 8b): This material is listed or exempted.

SARA 302/304: No products were found.

SARA 311/312 Hazards identification: Sudden release of pressure, Delayed (chronic)

health hazard

State regulations

: Connecticut Carcinogen Reporting: This material is not listed.

Connecticut Hazardous Material Survey: This material is not listed.

Florida substances: This material is not listed.

Illinois Chemical Safety Act: This material is not listed.

Illinois Toxic Substances Disclosure to Employee Act: This material is not listed.

Louisiana Reporting: This material is not listed.
Louisiana Spill: This material is not listed.
Massachusetts Spill: This material is not listed.
Massachusetts Substances: This material is listed.
Michigan Critical Material: This material is not listed.

**Minnesota Hazardous Substances**: This material is not listed. **New Jersey Hazardous Substances**: This material is listed.

New Jersey Spill: This material is not listed.

New Jersey Toxic Catastrophe Prevention Act: This material is not listed. New York Acutely Hazardous Substances: This material is not listed. New York Toxic Chemical Release Reporting: This material is not listed. Pennsylvania RTK Hazardous Substances: This material is listed. Rhode

Island Hazardous Substances: This material is not listed.

Canada

WHMIS (Canada) : Class A: Compressed gas.

**CEPA Toxic substances**: This material is not listed.

Canadian ARET: This material is not listed. Canadian NPRI: This material is not listed.

Alberta Designated Substances: This material is not listed.

Ontario Designated Substances: This material is not listed.

Quebec Designated Substances: This material is not listed.

## Section 16. Other information

#### **United States**

Label requirements

: GAS:

CONTENTS UNDER PRESURE.

Do not puncture or incinerate container.

Can cause rapid suffocation. May cause severe frostbite.

LIQUID:

Extremely cold liquid and gas under pressure.

Can cause rapid suffocation. May cause severe frostbite.


#### Canada

Build 1.1 Page: 5/6

**Label requirements** 

: Class A: Compressed gas.

# Hazardous Material Information System (U.S.A.)



### liquid:



# National Fire Protection Association (U.S.A.)



### liquid:



### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Build 1.1 Page: 6/6